



Silage and Grain Trailers



NC Engineering offer a selection of Silage/Grain trailers ranging from 10-25 Ton capacity. The monocoque body comes with a 100mm front to rear taper and tips to an angle of 50 degrees to ensure easy emptying.



All trailers are fitted as standard with a sprung drawbar, tandem spring suspension, hydraulic brakes, handbrake, full RTA approved lights (including rear beacon) and front galvanised ladder.



| | 10T Grain Trailer 16'x4'6" | 12T Grain Trailer 18'x4'6" | 13T Grain Trailer 16'x5'6" | 14T Grain Trailer 18'x5'6" | 14T Grain Trailer 20'x5' | 16T Grain Trailer 20'x5'6" | 16T Grain Trailer 22'x5' | 18T Grain Trailer 22'x5'6" |
|--|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-----------------------------|-------------------------------|-----------------------------|-------------------------------|
| Overall Length (A) | 6.76m | 7.37m | 6.76m | 7.37m | 7.99m | 7.99m | 8.59m | 8.59m |
| Overall Height (Grain Trailer) (B) | 2.59m | 2.59m | 2.91m | 2.91m | 2.76m | 2.91m | 2.76m | 2.91m |
| Body Length (C) | 5.01m | 5.62m | 5.01m | 5.62m | 6.23m | 6.23m | 6.84m | 6.84m |
| Platform Height (D) | 1.22 | 1.22m | 1.24m | 1.24m | 1.24m | 1.24m | 1.24m | 1.24m |
| Height from floor to top of grain side (E) | 1.37m | 1.37m | 1.67m | 1.67m | 1.52m | 1.67m | 1.52m | 1.67m |
| Overall body width - Rear (F) | 2.54m | 2.54m | 2.54m | 2.54m | 2.54m | 2.54m | 2.54m | 2.54m |
| Max tipping height grain trailer (G) | 5.75m | 6.24m | 5.97m | 6.45m | 6.88m | 6.97m | 7.27m | 7.37m |
| Grain Trailer Capacity | 14.63m ³ | 16.48m ³ | 17.9m ³ | 20.15m ³ | 20.37m ³ | 22.41m ³ | 22.42m ³ | 24.67m ³ |
| Overall height 8'x8' Silage Trailer | 3.66m | 3.66m | 3.68m | 3.68m | 3.68m | 3.68m | 3.68m | 3.68m |
| Height from floor to top of silage side | 2.44m | 2.44m | 2.44m | 2.44m | 2.44m | 2.44m | 2.44m | 2.44m |
| Floor Thickness | 5mm | 5mm | 5mm | 5mm | 5mm | 5mm | 5mm | 5mm |
| Side Thickness | 4mm | 4mm | 4mm | 4mm | 4mm | 4mm | 4mm | 4mm |



NC ENGINEERING (HAMILTONSBAWN) LTD

2 Killyrudden Road, Hamiltonsbawn, Richhill, Co. Armagh, N. Ireland BT61 9SF

Tel: 028 3887 1970 Fax: 028 3887 0362

E.mail:info@nc-engineering.com website: www.nc-engineering.com

In accordance with our policy of continued development we reserve the right to alter specifications and designs without notice



WHERE QUALITY COMES FIRST



Silage and Grain Trailers



Optional extras :-

- 3'6", 4' or 4'6" sides in-lieu of standard
- Self-locking hydraulic rear doors
- Rubber sealed door
- Roll over cover c/w long winding handle
- Fitted weather sheet
- Silage sides 8' both sides
- Silage sides 7'6" low side & 8' high side
- Hydraulically folding top side for root crop trailer
- High speed axles on 10 and 12 Ton models
- Dual air/hydraulic brakes
- Air only/hydraulic brakes
- Loadsensing
- ABS
- Hydraulic/electric brake away
- Adjustable hitch
- Swivel hitch
- Rear tow hitch c/w light socket
- Full width front window
- Lockable toolbox
- Colour to your requirements

The 10 and 12 Ton models are fitted with a 40kph axle while 13 -25 Ton models are fitted with high speed axles with 420x180 brake drums as standard. Standard wheel is the 385/65x22.5 super single. All trailers are fitted with an automatic top hinged tail door, complete with grain chute and manual securing bar. **See optional extras**